

① The Metal-Press-Fitting

Universal connection-technology from 16 mm up to 110 mm by MULTITUBO systems.

② The PPSU-Press-Fitting

The economical extension to the Metal-Press-Fitting range from 16 mm up to 32 mm.

③ The Metal-Push-Fitting

Invincible where press-tools cannot be used or where a rapid installation progress is required – from 16 mm up to 32 mm.

④ The PPSU-Push-Fitting

As fast as the Metal-Push-Fitting, with the same safety features, but a still more economic alternative.

With PROTECTOR-Ring

The PROTECTOR-Ring prevents insertion of non-calibrated pipes and thus damage of the O-Rings.



⑤ The Welding-Fitting

This cost efficient connection is perfect solution for acrid conditions. With an increased resistance against salt and many other corrosives*, the Welding-Fitting is the new alternative.

made in germany

⑥ Multilayer Pipes

With more than 30 years of expertise in the development and production of multilayer pipes, our pipes are an equivalent to highest quality. This enables MULTITUBO systems to offer 5 connection techniques, fully compatible within the same dimension.

A unique advantage that allows the highest possible flexibility at each building site.

**ALU
MULTI-LAYER PIPE**

**+ PRESS-FITTING
+ PUSH-FITTING
+ WELD-FITTING**

= 1 SYSTEM

We developed five different connection types, each with its own strength. So the installer can always select the optimal way to complete his installation.

And the best of the MULTITUBO systems is: All these connections are fully compatible within their dimension range. That's the way of success.

PIPES



Multi-layer Pipe PE-RT/AL/PE-RT, white, coils

MULTITUBO systems multi-layer pipe, according to ISO 21003, absolutely diffusion tight. Application: Installation of tap water- and heating-systems.


Art.-No.:	Type	Unit	Palet
10011	16 x 2,00	100 m	2.000 m
10010	16 x 2,00	200 m	2.600 m
10015	16 x 2,00	500 m	3.000 m
10020	18 x 2,00	200 m	2.600 m
10030	20 x 2,25	100 m	1.300 m
10040	25 x 2,50	50 m	650 m
10050	32 x 3,00	25 m	325 m
10051	32 x 3,00	50 m	500 m



Multi-layer Pipe PE-RT/AL/PE-RT, red, coils

MULTITUBO systems multi-layer pipe, absolutely diffusion tight. Application: Installation of panel heating ($t_{max} : 60\text{ }^{\circ}\text{C}$, $p_{max} : 6\text{ bar}$).
Now extra thin aluminium layer (AL = 0,15 mm), for more flexibility and easier handling.

Art.-No.:	Type	Unit	Palet
12010	16 x 2,00	200 m	2.600 m
12015	16 x 2,00	500 m	3.000 m




Multi-layer Pipe, PE-RT/AL/ PE-RT, white, lengths

MULTITUBO systems multi-layer pipe, absolutely diffusion tight. Application: Installation of tap water- and heating-systems. Supplied in straight lengths of 5 m / 3 m.

Art.-No.:	Type	Length	Unit
15012	16 x 2,00	5 m	125 m
15010	16 x 2,00	5 m	60 m
15030	20 x 2,25	5 m	85 m
15040	25 x 2,50	5 m	50 m
15050	32 x 3,00	5 m	35 m
15060	40 x 4,00	5 m	20 m
15070	50 x 4,50	5 m	10 m
15080	63 x 6,00	5 m	15 m
15090	75 x 7,50	5 m	5 m
15100	90 x 8,50	5 m	5 m
15110	110 x 10,00	5 m	5 m

Art.-No.:	Type	Length	Unit
15013	16 x 2,00	3 m	75 m
15031	20 x 2,25	3 m	51 m
15041	25 x 2,50	3 m	30 m
15051	32 x 3,00	3 m	21 m
15061	40 x 4,00	3 m	12 m
15071	50 x 4,50	3 m	6 m
15081	63 x 6,00	3 m	9 m
15091	75 x 7,50	3 m	3 m
15101	90 x 8,50	3 m	3 m
15111	110 x 10,00	3 m	3 m



Multi-layer Pipe, white, in protective tube, red

MULTITUBO systems multi-layer pipe, in corrugated protective tube made of PE-HD.

Art.-No.:	Type	Unit	Palet
16110R	16 x 2,00	75 m	975 m
16130R	20 x 2,25	75 m	675 m
16140R	25 x 2,50	50 m	450 m



Multi-layer Pipe, white, in protective tube, blue

MULTITUBO systems multi-layer pipe, in corrugated protective tube made of PE-HD.

Art.-No.:	Type	Unit	Palet
16110B	16 x 2,00	75 m	975 m
16130B	20 x 2,25	75 m	675 m
16140B	25 x 2,50	50 m	450 m



Multi-layer Pipe, white, in protective tube, black

MULTITUBO systems multi-layer pipe, in corrugated protective tube made of PE-HD.

Art.-No.:	Type	Unit	Palet
16110	16 x 2,00	75 m	975 m
16130	20 x 2,25	75 m	675 m



Multi-layer Pipe Plus S4, white, insulation blue, coils

MULTITUBO systems multi-layer pipe, with round insulation, thickness of insulation 4 mm, heat conductance rate (WLG) 040.

Art.-No.:	Type	Unit	Palet
14110	16 x 2,00	100 m	800 m
14111	16 x 2,00	50 m	750 m
14130	20 x 2,25	100 m	800 m
14131	20 x 2,25	50 m	750 m



Multi-layer Pipe Plus S4, white, insulation red, coils

MULTITUBO systems multi-layer pipe, with round insulation, thickness of insulation 4 mm, heat conductance rate (WLG) 040.

Art.-No.:	Type	Unit	Palet
14110R	16 x 2,00	100 m	800 m
14111R	16 x 2,00	50 m	750 m
14130R	20 x 2,25	100 m	800 m
14131R	20 x 2,25	50 m	750 m