



TP Threaded reducing nipple R PVC-U

R-R (inch)	PN (bar)	Code	SP	GP	Weight (kg)	L1 (mm)	L2 (mm)	H (mm)	O (mm)
1/2 - 3/8	16	RV0NRF20A	10	400	0.010	15.0	11.4	38	24
3/4 - 1/2	16	RV0NRF25B	10	280	0.017	16.3	15.0	43	30
1 - 3/4	16	RV0NRF32C	10	180	0.025	19.1	16.3	47	36
1 1/4 - 1	16	RV0NRF40D	1	150	0.044	21.4	19.1	56	46
1 1/2 - 1 1/4	16	RV0NRF50E	1	100	0.049	21.4	21.4	58	50
2 - 1 1/2	16	RV0NRF63F	1	130	0.081	25.7	21.4	62	65
2 1/2 - 2	16	RV0NRF75G	1	110	0.137	30.2	25.7	73	80
3 - 2 1/2	16	RV0NRF90H	1	50	0.207	33.3	30.2	82	95
4 - 3	16	RV0NRF91I	1	36	0.338	39.3	33.3	90	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>