



## Reducing bush PVC-C metric Rp

### Model:

- With solvent cement spigot metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	L (mm)
20	Rp	3/8	16	<b>723 910 434</b>	10	0.016	7	25	35
25	Rp	1/2	16	<b>723 910 437</b>	10	0.022	7	30	41
32	Rp	3/4	16	<b>723 910 441</b>	10	0.033	15	35	48
40	Rp	1	16	<b>723 910 446</b>	10	0.061	20	45	56
50	Rp	1 1/4	16	<b>723 910 452</b>	10	0.105	20	55	66
63	Rp	1 1/2	16	<b>723 910 458</b>	5	0.161	10	62	77

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>