






**SYGEF Plus flange adaptor jointing face serrated
SDR33/PN10
High Purity clean-room product ISO Class 5 (100)**

Model:

- Material: PVDF-HP



d (mm)	DN (mm)	PN (bar)	FM	Type	Code	Weight (kg)
90	80	10	BCF, IR	B	735 798 888	0.361
110	100	10	BCF, IR	A	735 798 889	0.471
125	100	10	IR	A	735 798 590	0.515
140	125	10	IR	A	735 798 891	0.738
160	150	10	IR	C	735 798 892	0.929
200	200	10	IR	C	735 798 894	1.704
225	200	10	IR	A	735 798 895	1.603
250	250	10	IR	C	735 798 596	2.730
280	250	10	IR	A	735 798 597	2.715
315	300	10	IR	C	735 798 598	3.657
355	350	10	IR	A	735 798 549	6.572
400	400	10	IR	C	735 798 550	7.970

d (mm)	L (mm)	L1 (mm)	L2 (mm)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	e (mm)
90	81	12	4	105	138	78	133	2.8
110	81	13		125	158	100		3.4
125	82	14		132	158	114		3.9
140	90	16		155	188	127		4.3
160	93	17		175	212	151		4.9
200	102	22		232	268	207		6.2
225	102	22		235	268	207		6.9
250	120	22		285	320	249		7.7
280	120	22		291	320	249		8.6
315	120	22		335	370	300		9.7
355	170	30		373	430	330		10.9
400	175	32		427	482	396		12.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>