



JRGUMAT Thermostatic mixing valve gunmetal

- Temperature: max. 90°C
 - Factory setting: 25 / 40 / 48 / 55 / 70°C (adjustable)
 - Material: gunmetal
 - Connection: male thread
- *as long as stock last

DN (mm)	Thread Type	Size (inch)	range (°C)	Temperature (°C)	JRG Code	GF Code	SP	Weight (kg)
15	GN	1/2	20 - 30	25	3400.910	350 760 511	1	0.530
15	GN	1/2	30 - 45	40	3400.912	350 760 512	1	0.530
*	15	GN	36 - 53	48	3400.914	350 760 517	1	0.530
15	GN	1/2	45 - 65	55	3400.916	350 760 513	1	0.530
15	GN	1/2	60 - 80	70	3400.918	350 760 514	1	0.530
20	GN	3/4	20 - 30	25	3400.920	350 760 411	1	0.700
20	GN	3/4	30 - 45	40	3400.922	350 760 412	1	0.700
*	20	GN	36 - 53	48	3400.924	350 760 417	1	0.670
20	GN	3/4	45 - 65	55	3400.926	350 760 413	1	0.700
20	GN	3/4	60 - 80	70	3400.928	350 760 414	1	0.701
25	GN	1	20 - 30	25	3400.930	350 760 311	1	0.910
25	GN	1	30 - 45	40	3400.932	350 760 312	1	0.910
*	25	GN	36 - 53	48	3400.934	350 760 317	1	0.910
25	GN	1	45 - 65	55	3400.936	350 760 313	1	0.910
25	GN	1	60 - 80	70	3400.938	350 760 314	1	0.910
32	GN	1 1/4	20 - 30	25	3400.940	350 760 211	1	1.630
32	GN	1 1/4	30 - 45	40	3400.942	350 760 212	1	1.630
*	32	GN	36 - 53	48	3400.944	350 760 217	1	1.590
32	GN	1 1/4	45 - 65	55	3400.946	350 760 213	1	1.630
32	GN	1 1/4	60 - 80	70	3400.948	350 760 214	1	1.590
40	GN	1 1/2	20 - 30	25	3400.950	350 760 111	1	2.140
40	GN	1 1/2	30 - 45	40	3400.952	350 760 112	1	2.140
*	40	GN	36 - 53	48	3400.954	350 760 117	1	2.140
40	GN	1 1/2	45 - 65	55	3400.956	350 760 113	1	2.140
40	GN	1 1/2	60 - 80	70	3400.958	350 760 114	1	2.100
50	GN	2	20 - 30	25	3400.960	350 760 011	1	3.510
50	GN	2	30 - 45	40	3400.962	350 760 012	1	3.510
*	50	GN	36 - 53	48	3400.964	350 760 017	1	3.510
50	GN	2	45 - 65	55	3400.966	350 760 013	1	3.510
50	GN	2	60 - 80	70	3400.968	350 760 014	1	3.510

DN (mm)	Thread Type	d2 G (inch)	d3 G (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	PN (bar)	⊙ (mm)
15	GN	1 1/8			47	35	90	35	55	10	5
15	GN	1 1/8			47	35	90	35	55	10	5
*	15	GN	1 1/8		47	35	90	35	55	10	5
15	GN	1 1/8			47	35	90	35	55	10	5
15	GN	1 1/8			47	35	90	35	55	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
*	20	GN	1 1/4	1/2	32	49	100	40	60	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
*	25	GN	1 1/2	3/4	36	51	110	43	67	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
32	GN	2	3/4	41	75	52	130	52	78	10	8
32	GN	2	3/4	41	75	52	130	52	78	10	8
*	32	GN	2	3/4	41	75	130	52	78	10	8

Data sheet

valid from: 11/13/23



	DN (mm)	Thread Type	d2 G (inch)	d3 G (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	PN (bar)	⊙ (mm)
	32	GN	2	¾	41	75	52	130	52	78	10	8
	32	GN	2	¾	41	75	52	130	52	78	10	8
	40	GN	2 ¼	¾	50	77	58	150	58	92	10	8
	40	GN	2 ¼	¾	50	77	58	150	58	92	10	8
*	40	GN	2 ¼	¾	50	77	58	150	58	92	10	8
	40	GN	2 ¼	¾	50	77	58	150	58	92	10	8
	40	GN	2 ¼	¾	50	77	58	150	58	92	10	8
	50	GN	2 ¾	¾	60	85	70	180	70	110	10	8
	50	GN	2 ¾	¾	60	85	70	180	70	110	10	8
*	50	GN	2 ¾	¾	60	85	70	180	70	110	10	8
	50	GN	2 ¾	¾	60	85	70	180	70	110	10	8
	50	GN	2 ¾	¾	60	85	70	180	70	110	10	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>