



## TP Flange adapter serrated PVC-U Inch BS

| d<br>(inch) | DN<br>(mm) | PN<br>(bar) | Code             | SP  | GP  | Weight<br>(kg) | Z<br>(mm) | L<br>(mm) | S<br>(mm) | E<br>(mm) |
|-------------|------------|-------------|------------------|-----|-----|----------------|-----------|-----------|-----------|-----------|
| 1/2         |            | 16          | <b>RV0QRL200</b> | 10  | 400 | 0.009          | 3         | 17        | 6         | 34        |
| 3/4         |            | 16          | <b>RV0QRL250</b> | 10  | 300 | 0.015          | 3         | 20        | 7         | 41        |
| 1           |            | 16          | <b>RV0QRL320</b> | 10  | 200 | 0.024          | 3         | 23        | 7         | 50        |
| 1 1/4       |            | 16          | <b>RV0QRL400</b> | 150 |     | 0.035          | 3         | 27        | 8         | 61        |
| 1 1/2       |            | 16          | <b>RV0QRL500</b> | 140 |     | 0.066          | 2         | 30        | 8         | 73        |
| 2           |            | 16          | <b>RV0QRL630</b> | 90  |     | 0.105          | 4         | 36        | 9         | 90        |
| 2 1/2       | 65         | 16          | <b>RV0QRI750</b> | 50  |     | 0.167          | 3         | 44        | 10        | 106       |
| 3           |            | 16          | <b>RV0QRL900</b> | 38  |     | 0.286          | 3         | 51        | 11        | 125       |
| 4           |            | 16          | <b>RV0QRL910</b> | 24  |     | 0.375          | 6         | 63        | 12        | 150       |
| 5           | 125        | 16          | <b>RV0QRI930</b> | 20  |     | 0.793          | 5         | 76        | 14        | 188       |
| 6           |            | 16          | <b>RV0QRL940</b> | 15  |     | 0.877          | 5         | 90        | 16        | 213       |
| 8           |            | 10          | <b>RV0QRL970</b> | 6   |     | 1.700          | 6         | 116       | 19        | 274       |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>