




SYGEF Standard fixed flange For socket fusion metric
Combined jointing face: flat and serrated

Model:

- Material: PVDF
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10

AL: number of holes



d	DN	PN	Inch	Code	Weight	D1	D2	D3	D4	H	H1	AL	z
(mm)	(mm)	(bar)	(inch)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)
20	15	16	1/2	735 740 106	0.121	27	65	93	14	12	19	4	5
25	20	16	3/4	735 740 107	0.162	33	75	103	14	13	21	4	4
32	25	16	1	735 740 108	0.229	40	85	115	14	14	23	4	4
40	32	16	1 1/4	735 740 109	0.340	50	100	137	18	15	25	4	4
50	40	16	1 1/2	735 740 110	0.409	61	110	147	18	16	27	4	4
63	50	16	2	735 740 111	0.551	76	125	162	18	18	31	4	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>