



**SYGEF Plus Adaptor nipple With male thread R  
SDR21/PN16  
High Purity clean-room product ISO Class 5 (100)**

**Model:**

- Material: PVDF-HP
- With taper male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF
- Avoid stresses when installing and large changes in temperature

| d    | Thread Type | Size   | PN    | FM      | Code               | Weight | L    | L1   | s    | e    |
|------|-------------|--------|-------|---------|--------------------|--------|------|------|------|------|
| (mm) |             | (inch) | (bar) |         |                    | (kg)   | (mm) | (mm) | (mm) | (mm) |
| 20   | R           | ½      | 16    | BCF, IR | <b>735 910 706</b> | 0.039  | 53   | 28   | 32   | 1.9  |
| 25   | R           | ¾      | 16    | BCF, IR | <b>735 910 707</b> | 0.021  | 55   | 28   | 36   | 1.9  |
| 32   | R           | 1      | 16    | BCF, IR | <b>735 910 708</b> | 0.034  | 57   | 28   | 46   | 2.4  |
| 40   | R           | 1 ¼    | 16    | BCF, IR | <b>735 910 709</b> | 0.058  | 60   | 28   | 55   | 2.4  |
| 50   | R           | 1 ½    | 16    | BCF, IR | <b>735 910 710</b> | 0.087  | 63   | 28   | 65   | 3.0  |
| 63   | R           | 2      | 16    | BCF, IR | <b>735 910 711</b> | 0.118  | 69   | 29   | 75   | 3.0  |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>