



PROGEF Natural Sanitary adaptor SDR11/PN10 Connection to 3A standard

Model:

- Stainlesssteel reinforcement ring
- Bead and Crevice Free weldable with the new BCF® Plus fusion machine
- Infrared-(IR Plus®) compatible. Choose fusion parameters: PP-n (PP-R)
- Material: PP-R unpigmented
- Conventional butt-welding according to DVS 2207

* Without stainless steel reinforcement ring

	d	Size	SDR	PN	FM	Code	Weight	L	D1	D3	e
	(mm)	(inch)		(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
*	20	¾	11	10	BCF, IR	728 598 207	0.006	49	25	16	1.9
	25	1	11	10	BCF, IR	728 598 209	0.031	50	50	22	2.3
	32	1 ½	11	10	BCF, IR	728 598 213	0.032	53	50	35	2.9
	40	1 ½	11	10	BCF, IR	728 598 215	0.033	54	50	35	3.7
	50	2	11	10	BCF, IR	728 598 217	0.062	61	64	48	4.6
	63	2 ½	11	10	BCF, IR	728 598 219	0.093	67	78	60	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>