


Tee 90° Reduced PE100 SDR11



- 10 bar Gas / 16 bar Water
- For further information on articles to GIS please contact your local sales office
- Moulded
- Usable with all types of electrofusion couplers
- Class C 7 bar Gas / 16 bar Water
- 10 bar Gas / 16 bar Water
- See general information for maximum allowable operating pressure
- **PE 100 SDR 11** (ISO S5)
- Long spigot version
- WRAS / GIS Approved
- * With welded reducer

Model:

- Moulded
- 10 bar Gas / 16 bar Water

d	d1	Part No.	weight	z	z1	L	L1	e	e1
(mm)	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	40	753 201 026	0.312	230	107	67	58	6	3.7
63	50	753 201 044	0.305	216	103	60	56	6	4.6
75	32	753 201 045	0.519	258	106	70	46	7	2.9
75	50	753 201 046	0.531	257	110	70	56	7	4.6
75	63	753 201 047	0.554	252	117	70	63	7	5.8
90	50	753 201 027	0.794	280	120	79	55	8	4.6
90	63	753 201 029	0.775	282	127	79	63	8	5.8
90	75	753 201 030	0.779	272	138	73	68	8	6.8
110	63	753 201 028	1.409	322	148	87	63	10	5.8
110	75	753 201 031	1.221	305	148	83	68	10	6.8
110	90	753 201 032	1.275	322	164	86	79	10	8.2
125	90	753 201 048	1.717	332	168	109	89	11	8.2
125	110	753 201 033	1.909	340	167	90	83	11	10.0
160	63	753 201 034	2.680	416	174	105	65	15	5.8
160	75	753 201 035	2.676	344	179	101	76	15	6.8
160	90	753 201 036	2.775	415	190	101	79	15	8.2
160	110	753 201 037	3.300	415	200	101	82	15	10.0
180	90	753 201 049	4.410	420	200	136	97	16	8.2
180	110	753 201 050	4.379	430	206	145	101	16	10.0
180	160	753 201 038	4.715	414	203	105	94	16	14.6
200	63	753 201 073	7.300	503	196	122	63	18	5.8
200	90	753 201 074	9.730	500	216	122	79	18	8.2
200	110	753 201 075	7.120	505	219	122	82	18	10.0
200	160	753 201 076	9.730	500	237	122	98	18	14.6
225	75	753 201 039	9.880	560	219	120	70	21	6.8
225	90	753 201 040	6.633	555	228	120	80	21	8.2
225	110	753 201 041	10.010	559	238	120	82	21	10.0
225	160	753 201 042	8.095	555	258	120	98	21	14.6
225	180	753 201 043	9.375	559	284	120	105	21	16.4
250	110	753 201 078	11.820	584	284	130	82	23	10.0
250	160	753 201 079	12.302	586	266	127	98	23	14.6
315	110	753 201 051	15.300	705	282	150	82	29	10.0
315	160	753 201 052	22.998	705	301	150	102	29	14.6
315	225	753 201 053	20.011	658	335	170	145	29	20.5
315	250	753 201 054	24.243	695	331	150	130	29	22.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 1/6/20



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>