





Flange adaptor PVC-U Joining face with O-ring groove metric

Model:

- Solvent cement socket metric
- Counterpart: flange adaptor flat code no. 721 800 105-721 790 111-125, combined flange adaptor (d160, d200, d225, d280, d315)
- Gasket: O-ring EPDM code no. 748 410 000-176, FKM code no. 749 410 000-176
- Flange: PVC-U code no. 721 700 005-138, PP/steel code no. 727 700 206-223, PP-V for socket systems metric code no. 727 700 406-423

d (inch)	d (mm)	DN (mm)	PN (bar)	Code	SP	Weight (kg)	D (mm)	D1 (mm)	d1 (mm)	L (mm)	L1 (mm)	z (mm)
	16	10	16	721 810 105	10	0.008	22	29	13	20	9	6
	20	15	16	721 810 106	10	0.011	27	34	16	22	9	6
	25	20	16	721 810 107	10	0.018	33	41	21	25	10	6
	32	25	16	721 810 108	10	0.027	41	50	28	28	10	6
	40	32	16	721 810 109	10	0.046	50	61	36	34	13	8
	50	40	16	721 810 110	10	0.068	61	73	45	39	13	8
	63	50	16	721 810 111	10	0.120	77	90	57	46	14	8
2 ½	75	65	16	721 810 112	10	0.183	91	106	69	52	15	8
	90	80	16	721 810 113	10	0.286	108	125	82	61	16	10
	110	100	16	721 810 114	10	0.478	131	150	102	72	18	11
	125	125	16	721 810 115	5	0.607	148	170	117	80	19	11
5	140	125	16	721 810 116	6	0.804	165	188	132	87	20	11
	160	150	16	721 810 117	2	1.226	188	213	152	97	22	11
	200	200	10	721 810 119	2	1.593	224	250	192	118	30	12
	225	200	10	721 810 120	2	1.878	248	274	217	131	31	12
	250	250	10	721 810 121	1	2.175	274	303	240	140	23	9
	280	250	10	721 810 122	1	3.170	308	329	270	158	30	13
	315	300	6	721 810 123	1	4.891	346	379	302	180	35	17

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>