



ecoFIT Reducing bush metric PE100
d20-50mm / SDR11 / Female thread Rp

Model:

- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes
- With fusion spigot metric and BSP parallel female thread, reinforced

d (mm)	Thread Type	Size (inch)	DN (mm)	PN (bar)	Code	Weight (kg)	Do (mm)	Lmax (mm)	z (mm)
20	Rp	3/8	15	10	733 910 434	0.012	26	33	7
25	Rp	1/2	20	10	733 910 437	0.015	31	37	6
32	Rp	3/4	25	10	733 910 441	0.028	36	43	8
40	Rp	1	32	10	733 910 446	0.046	45	49	9
50	Rp	1 1/4	40	10	733 910 452	0.071	55	55	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>