


TP Threaded adaptor Rp PVC-U



d (mm)	d (inch)	Rp (inch)	PN (bar)	Code	SP	GP	Weight (kg)	L (mm)	L1 (mm)	E (mm)	L2 (mm)
16		3/8	16	RV0AFP16A	10	600	0.009	22	14	23	11.4
20		1/2	16	RV0AFP20B	10	300	0.017	24	16	28	15.0
20		3/4	16	RV0AFP20C	10	240	0.022	24	16	34	16.3
25		1/2	16	RV0AFP25B	10	220	0.019	27	19	28	15.0
25		3/4	16	RV0AFP25C	10	200	0.023	27	19	34	16.3
25		1	16	RV0AFP25D	10	140	0.040	27	19	42	19.1
32		3/4	16	RV0AFP32C	10	180	0.028	30	22	34	16.3
32		1	16	RV0AFP32D	10	120	0.042	30	22	42	19.1
40		1	16	RV0AFP40D	1	100	0.049	36	26	42	19.1
40		1 1/4	16	RV0AFP40E	1	90	0.060	36	26	51	21.4
50		1 1/4	16	RV0AFP50E	1	70	0.075	41	31	51	21.4
50		1 1/2	16	RV0AFP50F	1	60	0.075	41	31	58	21.4
50		2	16	RV0AFP50G	1	100	0.119	41	31	72	25.7
63		2	16	RV0AFP63G	1	80	0.131	48	38	72	25.7
75		2	16	RV0AFP75G	1	72	0.170	53	44	72	25.7
75	2 1/2	2 1/2	16	RV0AFP75H	1	90	0.221	58	44	89	30.2
75		3	16	RV0AFP75I	1	100	0.293	58	44	103	33.3
90		2 1/2	16	RV0AFP90H	1	90	0.279	65	51	89	30.2
90		3	16	RV0AFP90I	1	60	0.308	65	51	103	33.3
90		4	16	RV0AFP90L	1	52	0.446	65	51	130	39.3
110		3	16	RV0AFP91I	1	45	0.376	76	61	103	33.3
110		4	16	RV0AFP91L	1	45	0.471	76	61	130	39.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>