




ecoFIT Bend 90° PE100
d50-500mm / SDR17

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100



d	DN	PN	FM	Code	Weight	Lmax	Q1	r	s1	z
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
50	40	10	IR	753 018 635	0.052	83.0	21	37.00	2.9	37
63	50	10	IR	753 018 636	0.087	97.5	21	45.00	3.6	45
75	65	10	IR	753 018 637	0.133	112.5	21	71.25	4.5	54
90	80	10	IR	753 018 638	0.226	135.0	22	85.50	5.4	68
110	100	10	IR	753 018 639	0.407	165.0	25	104.50	6.6	85
125	100	10	IR	753 018 515	0.556	187.5	28	116.00	7.3	97
140	125	10	IR	753 018 516	0.785	210.0	33	131.00	8.2	107
160	150	10	IR	753 018 517	1.156	240.0	33	151.00	9.4	127
180	150	10	IR	753 018 518	1.619	270.0	33	171.00	10.6	147
200	200	10	IR	753 018 519	2.208	300.0	33	190.00	11.7	167
225	200	10	IR	753 018 520	3.039	332.5	33	210.00	12.9	187
250	250	10		753 018 521	4.645	381.0	48	232.00	14.2	208
280	250	10		753 018 522	7.020	426.0	48	262.00	15.9	238
315	300	10		753 018 523	10.099	478.5	48	297.00	17.9	273
355	350	10		753 018 524	12.580	522.5	70	330.00	21.1	275
400	400	10		753 018 525	16.680	565.0	70	350.00	23.7	295
450	450	10		753 018 526	24.760	650.0	70	400.00	26.7	355
500	500	10		753 018 527	33.640	720.0	90	445.00	29.7	380

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>