



**SYGEF Plus Adaptor socket with female thread Rp
SDR21/PN16
High Purity clean-room product ISO Class 5 (100)**

Model:

- Material: PVDF-HP
- With butt fusion spigot and parallel female thread Rp
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

d (mm)	Thread Type	Size (inch)	PN (bar)	FM	Code	Weight (kg)	L (mm)	L1 (mm)	s (mm)	e (mm)	
20	Rp	¾	16	BCF, IR	735 910 785	0.030	54	30	32	1.9	
20	Rp	½	16	BCF, IR	735 910 786	0.026	54	30	32	1.9	
25	Rp	¾	16	BCF, IR	735 910 787	0.032	58	30	38	1.9	
32	Rp	1	16	BCF, IR	735 910 788	0.065	63	30	48	2.4	
40	Rp	1 ¼	16	BCF, IR	735 910 789	0.092	67	30	58	2.4	
50	Rp	1 ½	16	BCF, IR	735 910 790	0.108	67	30	65	3.0	
*	63	Rp	2	16	BCF, IR	735 910 791		73	30	80	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>