



Elbow 90° PVC-U metric Rp

Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d	Thread Type	Size	PN	Code	SP	Weight	z1	z2	D	L
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
12	Rp	1/4	16	721 100 204	10	0.010	7	7	20	19
16	Rp	3/8	16	721 100 205	10	0.015	9	9	25	23
20	Rp	1/2	16	721 100 206	10	0.023	13	11	30	27
25	Rp	3/4	16	721 100 207	10	0.035	16	15	35	33
32	Rp	1	16	721 100 208	10	0.060	19	19	45	39
40	Rp	1 1/4	16	721 100 209	10	0.122	23	27	55	50
50	Rp	1 1/2	16	721 100 210	5	0.187	27	36	62	58
63	Rp	2	16	721 100 211	10	0.324	33	46	75	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>