



**O-ring FKM white**  
**For unions with gap filling O-ring positioning**  
**High Purity clean-room product ISO Class 5 (100)**

**Model:**

- For unions with gap filling O-ring position
- Hardness approx. 65° Shore
- FKM white min. temperature -15°C

| d<br>(mm) | FKM<br>Code        | Weight<br>(kg) | D<br>(mm) | D1<br>(mm) | D2<br>(mm) |
|-----------|--------------------|----------------|-----------|------------|------------|
| 20        | <b>749 411 005</b> | 0.002          | 20.6      | 15.5       | 2.62       |
| 25        | <b>749 411 006</b> | 0.002          | 27.3      | 20.2       | 3.53       |
| 32        | <b>749 411 120</b> | 0.002          | 33.6      | 26.6       | 3.53       |
| 40        | <b>749 411 062</b> | 0.002          | 41.6      | 34.5       | 3.53       |
| 50        | <b>749 411 172</b> | 0.003          | 51.1      | 44.0       | 3.53       |
| 63        | <b>749 411 054</b> | 0.003          | 63.0      | 55.0       | 4.00       |
| 75        | <b>749 411 013</b> | 0.010          | 79.9      | 69.2       | 5.33       |
| 90        | <b>749 411 014</b> | 0.012          | 92.6      | 81.9       | 5.33       |
| 110       | <b>749 411 015</b> | 0.015          | 117.0     | 101.0      | 5.33       |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>