



SYGEF Standard adaptor socket female Rp SDR21/PN16

Model:

- Material: PVDF
- With butt fusion spigot and parallel female thread Rp
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

	d	Size	PN	FM	Thread Type	Code	SP	Weight	L	L1	s	e
	(mm)	(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)
	20	¾	16	BCF, IR	Rp	735 910 585	1	0.030	54	30	32	1.9
	20	½	16	BCF, IR	Rp	735 910 586	1	0.026	54	30	32	1.9
	25	¾	16	BCF, IR	Rp	735 910 587	1	0.032	58	30	38	1.9
	32	1	16	BCF, IR	Rp	735 910 588	1	0.065	63	30	48	2.4
	40	1 ¼	16	BCF, IR	Rp	735 910 589	1	0.092	67	30	58	2.4
	50	1 ½	16	BCF, IR	Rp	735 910 590	1	0.108	67	30	65	3.0
*	63	2	16	BCF, IR	Rp	735 910 591	1	0.195	73	30	80	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>