



TP Flange adaptor serrated PVC-U metric

- **DN** indicates the nominal diameter of the PVC pipe

d (mm)	d2 (mm)	DN (mm)	PN (bar)	Code	SP	GP	Weight (kg)	Z (mm)	L (mm)	E (mm)	S (mm)
20	27	15	16	RV0QRI200	10	360	0.011	3	16	34	6
25	33,2	20	16	RV0QRI250	10	300	0.017	3	19	41	7
32	41	25	16	RV0QRI320	10	200	0.026	3	22	50	7
40	50,5	32	16	RV0QRI400	1	140	0.038	3	26	61	8
50	61,5	40	16	RV0QRI500	1	140	0.059	3	31	73	8
63	76,5	50	16	RV0QRI630	1	90	0.104	3	38	90	9
75	90,5	65	16	RV0QRI750	1	50	0.167	3	44	106	10
90	108,5	80	16	RV0QRI900	1	38	0.274	5	51	125	11
110	131,5	100	16	RV0QRI910	1	24	0.440	5	61	150	12
125	146,5	110	16	RV0QRI920	1	25	0.560	5	69	168	13
140	164,5	125	16	RV0QRI930	1	20	0.793	5	76	188	14
160	187	150	16	RV0QRI940	1	15	1.035	5	86	213	16
200	229	200	16	RV0QRI960	1	8	1.823	7	106	254	18
225	248	200	10	RV0QRI970	6	6	1.762	7	119	274	19
250	273,5	250	10	RV0QRI980	1	4	2.326	10	131	307	20
315	344	300	10	RV0QRI991	1	3	4.834	11	164	379	27

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>