




ecoFIT Elbow 45° PE100
d50-225mm / SDR17

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100



d	DN	PN	FM	Code	Weight	Lmax	Q1	s1	z
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
50	40	10	IR	753 158 535	0.045	89.0	26	2.9	16
63	50	10	IR	753 158 536	0.091	102.0	29	3.6	18
75	65	10	IR	753 158 412	0.125	110.2	29	4.7	20
90	80	10	IR	753 158 413	0.198	129.1	34	5.6	23
110	100	10	IR	753 158 414	0.375	158.4	43	6.9	27
125	100	10	IR	753 158 540	0.542	179.1	48	7.1	31
140	125	10	IR	753 158 541	0.784	199.7	55	8.0	33
160	150	10	IR	753 158 542	1.190	227.3	60	9.1	40
200	200	10	IR	753 158 544	2.331	282.4	75	11.4	49
225	200	10	IR	753 158 545	3.282	318.5	85	12.8	55

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>