





Un produit installé
toutes les **6** secondes
dans le monde.




CIRCULAIRES A JOINTS



REDUCTIONS CONIQUES MALE/MALE															
REDV	Code	Ø A (mm)	Ø B (mm)	REDV	Code	Ø A (mm)	Ø B (mm)	REDV	Code	Ø A (mm)	Ø B (mm)	REDV	Code	Ø A (mm)	Ø B (mm)
REDV 100/80	865 698	100	80	REDV 315/160	865 690	315	160	REDV 450/315	866 468	450	315	REDV 560/500	866 480	560	500
REDV 125/80	865 699	125	80	REDV 315/200	865 691	315	200	REDV 450/355	866 469	450	355	REDV 630/355	866 481	630	355
REDV 125/100	866 313	125	100	REDV 315/250	866 463	315	250	REDV 450/400	866 470	450	400	REDV 630/400	866 482	630	400
REDV 160/80	866 343	160	80	REDV 355/200	866 464	355	200	REDV 500/250	866 471	500	250	REDV 630/450	866 483	630	450
REDV 160/100	866 344	160	100	REDV 355/250	866 465	355	250	REDV 500/315	866 472	500	315	REDV 630/500	866 484	630	500
REDV 160/125	867 835	160	125	REDV 355/315	866 466	355	315	REDV 500/355	866 473	500	355	REDV 630/560	866 485	630	560
REDV 200/100	866 345	200	100	REDV 400/200	865 693	400	200	REDV 500/400	866 474	500	400	REDV 710/400	866 486	710	400
REDV 200/125	865 686	200	125	REDV 400/250	865 694	400	250	REDV 500/450	866 475	500	450	REDV 710/450	866 487	710	450
REDV 200/160	865 687	200	160	REDV 400/315	865 695	400	315	REDV 560/315	866 476	560	315	REDV 710/500	866 488	710	500
REDV 250/125	865 697	250	125	REDV 400/355	865 696	400	355	REDV 560/355	866 477	560	355	REDV 710/560	866 489	710	560
REDV 250/160	865 688	250	160	REDV 450/250	866 467	450	250	REDV 560/400	866 478	560	400	REDV 710/630	866 490	710	630
REDV 250/200	865 689	250	200	-	-	-	-	REDV 560/450	866 479	560	450	-	-	-	-



BOUCHONS MALE											
BRTV	Code	Ø (mm)	BRTV	Code	Ø (mm)	BRTV	Code	Ø (mm)	BRTV	Code	Ø (mm)
BRTV 80	865 517	80	BRTV 200	865 521	200	BRTV 400	865 525	400	BRTV 630	865 529	630
BRTV 100	865 518	100	BRTV 250	865 522	250	BRTV 450	865 526	450	-	-	-
BRTV 125	865 519	125	BRTV 315	865 523	315	BRTV 500	865 527	500	-	-	-
BRTV 160	865 520	160	BRTV 355	865 524	355	BRTV 560	865 528	560	-	-	-



TESV SOUCHES INSONORISÉES * MALE/MALE															
TESV	Code	Ø A (mm)	Ø B (mm)	H (mm)	h (mm)	R (mm)	TESV	Code	Ø A (mm)	Ø B (mm)	H (mm)	h (mm)	R (mm)	TESV	Code
TESV 125	867 828	125	200	250	100	60	TESV 400	867 834	400	500	540	225	60	TESV 500	866 655
TESV 160	867 829	160	250	300	125	60	TESV 450	866 654	450	560	590	250	40	TESV 560	866 656
TESV 200	867 830	200	315	300	125	60	TESV 500	866 655	500	630	640	275	40	TESV 630	866 657
TESV 250	867 831	250	355	350	150	60	TESV 560	866 656	560	710	630	300	40	-	-
TESV 315	867 832	315	400	400	175	60	TESV 630	866 657	630	800	710	350	40	-	-
TESV 355	867 833	355	450	500	200	60	-	-	-	-	-	-	-	-	-

* Epaisseur laine de roche : 25 mm