



## O-ring EPDM/FKM

### Model:

- For unions and adaptor unions
- Hardness approx. 65° Shore
- EPDM minimum temperature -40°C
- FKM minimum temperature -15°C

\* For unions PVC-U, PVC-C and ABS: 21 51 01, 21 51 11, 21 53 03, 21 53 08, 21 55 04, 21 55 13, 21 55 18, 23 51 01 and 29 51 01 only

| d<br>(mm) | DN<br>(mm) | EPDM<br>Code   | Weight<br>(kg) | FKM<br>Code | Weight<br>(kg) |
|-----------|------------|----------------|----------------|-------------|----------------|
| 10 - 12   | 8          | 748 410 004    | 0.002          | 749 410 004 | 0.020          |
| 16        | 10         | 748 410 005    | 0.002          | 749 410 005 | 0.002          |
| 20        | 15         | 748 410 006    | 0.002          | 749 410 006 | 0.002          |
| 25        | 20         | 748 410 007    | 0.002          | 749 410 007 | 0.002          |
| 32        | 25         | 748 410 008    | 0.003          | 749 410 008 | 0.002          |
| 40        | 32         | 748 410 009    | 0.003          | 749 410 009 | 0.007          |
| 50        | 40         | 748 410 010    | 0.004          | 749 410 010 | 0.060          |
| 63        | 50         | 748 410 011    | 0.005          | 749 410 011 | 0.003          |
| *         | 90         | 80 748 410 248 | 0.002          | 749 410 248 | 0.020          |

| d<br>(mm) | D<br>(mm) | D1<br>(mm) | D2<br>(mm) | closest inch<br>(inch) |
|-----------|-----------|------------|------------|------------------------|
| 10 - 12   | 17.62     | 12.37      | 2.62       | ¼                      |
| 16        | 20.78     | 15.54      | 2.62       | ⅜                      |
| 20        | 27.28     | 20.22      | 3.53       | ½                      |
| 25        | 35.23     | 28.17      | 3.53       | ¾                      |
| 32        | 39.99     | 32.93      | 3.53       | 1                      |
| 40        | 51.33     | 40.65      | 5.34       | 1 ¼                    |
| 50        | 57.68     | 46.99      | 5.34       | 1 ½                    |
| 63        | 70.37     | 59.69      | 5.34       | 2                      |
| *         | 90        | 105.30     | 94.62      | 3                      |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>