



2345 : Hublots LED IP65



50 000 h L65 à 25 °C

Switch permettant d'avoir 3 flux lumineux différents
Hublot robuste IP65, plafonnier ou applique murale
+ HFS : avec détecteur de présence



CODE	RÉFÉRENCE	FLUX (lm)	PUISSANCE (W)	TEMPÉRATURE DE COULEUR (K)	UGR	DIMENSIONS (mm)	DIMMABLE
7376640	2345 WD1 20/14/10/ML-840 ET IP65	2 000 / 1 400 / 1 000	21/14/11	4000	22	Ø 300 x 85	NON
7376840	2345 WD1 20/14/10/ML-830 ET IP65	2 000 / 1 400 / 1 000	21/14/11	3000	22	Ø 300 x 85	NON
7376740	2345 WD1 20/14/10/ML-840 ET IP65 +HFS	2 000 / 1 400 / 1 000	21/14/11	4000	22	Ø 300 x 85	NON
7376940	2345 WD1 20/14/10/ML-830 ET IP65 +HFS	2 000 / 1 400 / 1 000	21/14/11	3000	22	Ø 300 x 85	NON



2350 G3 : Plafonniers LED



50 000 h L65 à 25 °C

Switch permettant d'avoir 2 flux lumineux différents
Version 8MC : multi-flux et multi-couleur



CODE	RÉFÉRENCE	FLUX (lm)	PUISSANCE (W)	TEMPÉRATURE DE COULEUR (K)	UGR	DIMENSIONS (mm)	DIMMABLE
7640840	2350 G3 D PW19 36/29/ML-8MC ET	3 600 / 2 900	33/25	4000/3000	19	625x625	NON
7755740	2350 G3 D2 PW19 40/30/ML-840 ET	4 000 / 3 000	36/30	4000	19	1225x325	NON
7755640	2350 G3 D2 PW19 40/30/ML-8MC ET	4 000 / 3 000	36/30	4000/3000	19	1225x325	NON
7755951	2350 G3 D2 PW19 4000-840 ETDD	4 000	36	4000	19	1225x325	OUI
7755851	2350 G3 D2 PW19 4000-8MC ETDD	3 700	36	4000/3000	19	1225x325	OUI
7756140	2350 G3 D3 PW19 60/40/ML-840 ET	6 000 / 4 000	54/38	4000	19	1525x325	NON
7756040	2350 G3 D3 PW19 60/40/ML-8MC ET	6 000 / 4 000	54/38	4000/3000	19	1525x325	NON
7756351	2350 G3 D3 PW19 6000-840 ETDD	6 000	54	4000	19	1525x325	OUI
7756251	2350 G3 D3 PW19 6000-8MC ETDD	6 000	54	4000/3000	19	1525x325	OUI



2360 : Luminaires suspendus LED



50 000 h L65 à 25 °C

Luminaire suspendu LED direct/indirect dimmable DALI
Livré avec câbles de suspension et d'alimentation
H1 : version 4000 lm, 1195 mm
H2 : version 6000 lm, 1495 mm



CODE	RÉFÉRENCE	FLUX (lm)	PUISSANCE (W)	TEMPÉRATURE DE COULEUR (K)	UGR	DIMENSIONS (mm)	DIMMABLE
7377640	2360 H1 PW19-IL 4000-840 ET	4 400	40	4000	16	1195x295	NON
7377651	2360 H1 PW19-IL 4000-840 ETDD	4 400	40	4000	16	1195x295	OUI
7377540	2360 H1 PW19-IL 4000-830 ET	4 400	40	3000	16	1195x295	NON
7377551	2360 H1 PW19-IL 4000-830 ETDD	4 400	40	3000	16	1195x295	OUI
7789940	2360 H2 PW19-IL 6000-830 ET	6 000	55	3000	16	1495x295	NON
7789951	2360 H2 PW19-IL 6000-830 ETDD	6 000	52	3000	16	1495x295	OUI
7790040	2360 H2 PW19-IL 6000-840 ET	6 000	55	4000	16	1495x295	NON
7790051	2360 H2 PW19-IL 6000-840 ETDD	6 000	52	4000	16	1495x295	OUI