




ecoFIT Union end PE100 d20-110mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared- (IR Plus) compatible.
- **For the dimensions d75-110 please see instructions for the installation**

*Only for variable area flow meters



d	DN	PN	FM	Code	Weight	Do	Lmax	Q1	s1
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
20	15	16	IR	753 508 606	0.011	30	53.5	38	1.9
25	20	16	IR	753 508 607	0.018	39	57.0	42	2.3
32	25	16	IR	753 508 608	0.027	45	59.5	41	2.9
40	32	16	IR	753 508 609	0.044	57	62.5	42	3.7
50	40	16	IR	753 508 610	0.061	63	65.5	44	4.6
63	50	16	IR	753 508 611	0.100	78	68.5	45	5.8
75	65	10	IR	753 608 612	0.147	101	66.0	34	6.8
*	75	65	10	700 246 420	0.300	101	66.0	34	6.8
90	80	10	IR	753 608 613	0.156	101	66.0	55	8.2
110	100	10	IR	753 608 614	0.226	121	66.0	55	10.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>