



SYGEF Standard adaptor socket female Rp SDR21/PN16

Model:

- Material: PVDF
- With butt fusion spigot and parallel female thread Rp
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

d	Thread Type	Size	DN	PN	SDR	FM	Sensor Type
(mm)		(inch)	(mm)	(bar)			
25	Rp	1 1/4	20	16	21	BCF, IR	pH/ORP: 272X, 277X- ISO Conductivity: 2839-1D - 2842-1D
40	Rp	1 1/2	32	16	21	BCF, IR	
50	Rp	1 3/4	40	16	21	BCF, IR	pH/ORP: 3719-12
*	Rp	2	50	16	21	BCF, IR	pH/ORP: 3719-22

d	Code	SP	Weight	e	L	s	L1
(mm)			(kg)	(mm)	(mm)	(mm)	(mm)
25	735 910 587	1	0.032	1.9	58	38	30
40	735 910 589	1	0.092	2.4	67	58	30
50	735 910 590	1	0.108	3.0	67	65	30
*	735 910 591	1	0.195	3.0	73	80	30

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>