




ecoFIT Union PE100 d20-110mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared- (IR Plus®) compatible
- Gasket: O-ring EPDM / FKM
- ecoFIT Union Nut Material: PP glass fiber reinforced
- For dimensions d75 -110, please follow the assembly instructions

d (mm)	DN (mm)	PN (bar)	FM	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
20	15	16	IR	753 518 606	0.048	753 528 606	0.042
25	20	16	IR	753 518 607	0.078	753 528 607	0.052
32	25	16	IR	753 518 608	0.108	753 528 608	0.083
40	32	16	IR	753 518 609	0.176	753 528 609	0.151
50	40	16	IR	753 518 610	0.241	753 528 610	0.196
63	50	16	IR	753 518 611	0.402	753 528 611	0.406
75	65	10	IR	753 518 612	0.537	753 528 612	0.520
90	80	10	IR	753 518 613	0.540	753 528 613	0.562
110	100	10	IR	753 518 614	0.783	753 528 614	0.760

d (mm)	Do (mm)	L1 (mm)	L2 (mm)	Lmax (mm)	Q1 (mm)	Q2 (mm)	G (inch)	e (mm)
20	48	54.0	53	107	26	38	1	1.9
25	58	57.0	56	113	26	42	1 1/4	2.3
32	65	60.0	59	119	25	41	1 1/2	3.0
40	79	63.0	63	126	25	42	2	3.7
50	91	65.0	65	131	25	44	2 1/4	4.6
63	111	69.0	68	137	25	45	2 3/4	5.8
75	135	66.0	66	132	24	34	S107,5x3,6	6.8
90	135	65.5	66	131	24	45	S107,5x3,6	8.2
110	158	65.5	66	131	25	40	S127,5x3,6	10.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>