



**SYGEF Plus Adaptor nipple with male thread NPT
SDR21/PN16
High Purity clean-room product ISO Class 5 (100)**

Model:

- Material: PVDF-HP
- With taper male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF
- Avoid stresses when installing and large changes in temperature

d	Thread Type	Size	PN	FM	Code	Weight	L	L1	s	e
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
20	NPT	½	16	BCF, IR	735 914 306	0.025	53	28	32	1.9
25	NPT	¾	16	BCF, IR	735 914 307	0.035	55	28	36	1.9
32	NPT	1	16	BCF, IR	735 914 308	0.053	57	28	46	2.4
40	NPT	1 ¼	16	BCF, IR	735 914 309	0.077	60	28	55	2.4
50	NPT	1 ½	16	BCF, IR	735 914 310	0.134	63	28	65	3.0
63	NPT	2	16	BCF, IR	735 914 311	0.119	69	29	75	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>