



PROGEF Standard Flange adaptor PP-H ANSI SDR11/PN10 Combined jointing face: flat and serrated

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR- Infrared welding compatible
- Suitable for flange connections to metric (from d110 also to ANSI/ASME B16.5)
- Suitable for flange connections to metric
- Injection moulded

Flange adaptors are designed to work with most butterfly valves
For bigger dimensions, see flange adaptors in other chapters

d	DN	PN	FM	Type	Code	Weight
(mm)	(mm)	(bar)				(kg)
25	20	10	IR	A	727 798 757	0.022
32	25	10	IR	A	727 798 758	0.039
40	32	10	IR	A	727 798 759	0.056
50	40	10	IR	A	727 798 760	0.087
90	80	10	IR	B	727 798 763	0.310

d	d1	d2	d3	d4	L	L1	L2	e	a
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
25	32	54		20	52	27	9	2.55	
32	40	63		26	54	28	10	3.15	
40	49	73		32	55	25	11	4.00	
50	60	82		40	62	32	12	4.95	
90	105	133	78	70	80	41	17	8.75	30

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>