

Des marques expertes
au service de votre quotidien




WATTS®

JOINTS POUR LES ROBINETS

Présentation en sachet




Code réf.	Marque	Ø ext. x épaisseur	Qté./sachet	Condit.
545111	Chaffoteaux	10,6 x 5	8	10
545511	Porcher	11 x 5	8	10
546211	Porcher	11,5 x 6	8	10
545211	E.L.M.	12 x 4	8	10
545011	Chaffoteaux	12,4 x 5	8	10
545012	Jacob Delafon	12,5 x 3	7	10
546311	Porcher	13 x 5	5	10
545611	Porcher	13 x 6	5	10
546511	Ideal Standard	13,5 x 5	5	10
546411	Porcher	14,5 x 6	5	10
545711	Bricard	15 x 5	5	10
546711	Jacob Delafon	15,5 x 4	5	10
545811	Dimpre	16 x 4	5	10
545311	Le Regent	16 x 6	5	10



Clapet percé standard EPDM

Pour eau chaude et froide sanitaire, air, acides non-oxydants, ozone.
 Excellente résistance à la compression. Bonne résistance au vieillissement.
 Température maxi : 125°C. Température mini : - 40°C.
 Vapeur (eau, air) : 125°C. Dureté shore A : 85 (+/- 5). Agrément ACS.



Présentation en vybac



Code réf.	Dimension	Ø int. x Ø ext. x ép.	Qté./vybac	Condit.
500920	n°4	4 x 10 x 5	50	1
500921	n°5	4 x 12 x 5	50	1
500922	n°6	4 x 14 x 5	50	1
500923	n°7	4 x 15 x 5	50	1
500924	n°8	4 x 16 x 5	50	1
500925	n°10	4 x 17 x 5	50	1
500926	n°12 B	4 x 18 x 5	50	1
500927	n°12 C	4 x 19 x 5	50	1
500928	n°12	4 x 20 x 5	50	1
500929	n°15 B	4 x 21 x 5	50	1
500930	n°15	5 x 22 x 6	25	1
013806	Assortiment 4x10x5(5)-4x12x5(5) 4x13x4(5)-5x13x5(5)-4x14x5(5) 4x16x4(5)-4x16x5(5)-4x17x5(5) 4x18x5(5)-4x20x5(5)		50	1

