



Adaptor bush equal PVC-U metric R

Model:

- With solvent cement socket metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
16	R	3/8	16	721 910 705	10	0.011	20	34	27
20	R	1/2	16	721 910 706	10	0.018	24	40	32
25	R	3/4	16	721 910 707	10	0.025	25	44	36
32	R	1	16	721 910 708	10	0.039	28	50	46
40	R	1 1/4	16	721 910 709	10	0.061	31	57	55
50	R	1 1/2	16	721 910 710	10	0.092	32	63	65
63	R	2	16	721 910 711	5	0.161	38	76	80
75	R	2 1/2	10	721 910 712	6	0.227	42	86	90
90	R	3	10	721 910 713	5	0.389	46	97	110
110	R	4	10	721 910 714	5	0.572	53	114	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>