



SYGEF Plus Adaptor socket

Installation fitting with female thread Rp SDR21/PN16

High Purity clean-room product ISO Class 5 (100)

Model:

- Material: PVDF-HP
- With butt fusion spigot and parallel female thread Rp
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

d	Thread Type	Size	DN	PN	SDR	FM	Sensor Type
(mm)		(inch)	(mm)	(bar)			
25	Rp	¾	20	16	21	BCF, IR	pH/ORP: 272X, 277X- ISO Conductivity: 2839-1D - 2842-1D
40	Rp	1 ¼	32	16	21	BCF, IR	
50	Rp	1 ½	40	16	21	BCF, IR	pH/ORP: 3719-12
*	Rp	2	50	16	21	BCF, IR	pH/ORP: 3719-22

d	Code	SP	Weight	L	L1	e	s
(mm)			(kg)	(mm)	(mm)	(mm)	(mm)
25	735 910 787	1	0.032	58	30	1.9	38
40	735 910 789	1	0.092	67	30	2.4	58
50	735 910 790	1	0.108	67	30	3.0	65
*	735 910 791	1		73	30	3.0	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>