

Series 1545

**PE-RT RBM Tita-fix multilayer pipe.**

Multilayer pipe for underfloor heating in polyethylene, aluminium and polyethylene. Welded aluminium layer type A

- Composition PE-RT/Al/PE-RT
- White
- Poper 10 Bar
- Tmal 95 °C
- Duration at operating conditions ~ 50 years
- Type: PE-RT

PE-RT RBM Tita-fix multilayer pipe in roll

Code	Pipe size (mm)	Aluminium th. (mm)	Roll (m)	Pack (m)	Pallet- (m)	Cat.
1545.16.00	16x2	0,20	100	100	1400	10.01
1545.16.20	16x2	0,20	250	250	2500	10.01
1545.16.10	16x2	0,20	500	500	3000	10.01
1545.20.00	20x2	0,30	100	100	1400	10.01
1545.20.10	20x2	0,30	250	250	1750	10.01
1545.20.50	20x2	0,30	500	500	2500	10.01
1545.26.00	26x3	0,40	50	1	550	10.01
1545.32.00	32x3	0,40	50	1	600	10.01
1545.40.00	40x3,5	0,50	25	1	300	10.01

Size: Outside Ø x pipe thickness

PE-RT RBM Tita-fix multilayer pipe in bars

Code	Pipe size (mm)	Aluminium th. (mm)	Bar (m)	Pack- (m)	Cat.
1546.16.00	16x2	0,20	4	100	10.01
1546.20.00	20x2	0,30	4	76	10.01
1546.26.00	26x3	0,40	4	40	10.01
1546.32.00	32x3	0,40	4	24	10.01
1546.40.00	40x3,5	0,50	5	50	10.01
1546.50.00	50x4	0,60	5	15	10.01
1546.63.00	63x4,5	0,80	5	5	10.01

Size: Outside Ø x pipe thickness

Certifications:

Compliant with: EN ISO 21003 - DM 174/04

