



Installation fitting type 314 PVC-U Weld on metric

Model:

- Threaded outlet 1 1/4" NPSM
- For conventional hot gas back welding according to DVS 2207 part 3

Attention:

- pH sensors can also be used for dimensions above d180/DN150 and below d75/DN65 with 721 314 000 The length might have to be adjusted (sensor has to touch the medium)
- only for pressureless or low pressure application
- pressure rate depends on quality of hot gas back welding
- please consult the instruction manual
- Installation by trained and certified welders only
- sensor length depends on installation fitting

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

d (mm)	DN	Code	SP	Weight (kg)	Sensor Type	D (mm)	L (mm)
75 - 180	65 - 150	721 314 000	1	0.054	flow X0, pH XX	38	68
200 - 355	200 - 350	721 314 001	1	0.078	flow X1	38	102
400 - 630	350 - 600	721 314 002	1	0.153	flow X2	38	178

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>