

Product data sheet

Specifications



Mureva Tube GT - GT conduit tuliped - diam. 25 mm - grey

IMT40225

Main

Range of product	Mureva
Product or component type	Rigid conduit
Shape	Tuliped ends
Function available	GT-function
Mounting location	Outdoor Indoor
Nominal cross section	359 mm²
Diameter	External: 25 mm Internal: 21.4 mm
Colour tint	Grey (RAL 7035)
Length	2 m

Complementary

Resistance to compression	750 N
Material	PVC (polyvinyl chloride)
Quantity per set	34 m
Ambient air temperature for operation	-5...60 °C
Standards	IEC 61386

Environment

IK degree of protection	IK07
Product certifications	NF
Environmental characteristic	Non-flame propagating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	301.0 g
Package 1 Height	2.5 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Package 1 width	2.5 cm
Package 1 Length	200.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)

IMT40225 is replaced by:

1x		GT conduit tuliped, Mureva Tube GT, diameter 25 mm 2m, DIY, grey IMT50225
----	---	--